

Technical drawing of a mail unit showing front and side elevations with dimensions.

Front Elevation Dimensions:

- Overall Width: 31 9/16" ACTUAL
- Internal Width (R.O.): 30 5/8" MAX, 30 3/8" MIN
- Overall Height: 37 1/4" ACTUAL
- Height to Tenant Lock: 60 3/4"
- Height to Access Door Lock: 43 1/4"
- Height to Bottom Shelf: 28"

Side Elevation Dimensions:

- Depth: 17" R.O. DEPTH
- Height to Tenant Lock: 36 5/8" MAX, 36 3/8" MIN R.O.
- Height from Finished Floor to Bottom of R.O.: 27 1/8"

Labels:

- FINISHED FLOOR
- TO TENANT LOCK
- TO ACCESS DOOR LOCK
- TO BOTTOM SHELF

DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE	QTY.
MAILBOX	MB2	6-1/2" H x 12" W x 15" D	6
OUTGOING MAIL	OM2	6-1/2" H x 12" W x 15" D	1
PARCEL	PL6	20-1/2" H x 12" W x 15" D	1

1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
 - a. At least one customer compartment shall be positioned less than 48" above finished floor (AFF).
 - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
 - c. No patron (tenant) lock shall be positioned more than 67" AFF.
 - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
 - e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
2. This 4C mailbox can also be used for private applications.
3. The rough opening width for multi-unit 4C installations is provided using the Florence configurator: www.florencemailboxes.com/configurator.

PRODUCT SERIES: VERSATILE™ 4C FRONT LOAD MAILBOX

MODEL	4C10D-06	REV	E
SCALE	NONE	LAST REV DATE	06/29/19
DRAWING NUMBER		DRAWN BY	
4C10D-06CS		RAK	