


versatile™ 4C Mailbox, 4C11D-19



COMPARTMENT CHART

| DESCRIPTION | COMPARTMENT | COMPARTMENT SIZE | QTY. |
|---------------|-------------|-----------------------|------|
| MAILBOX | MB1 | 3" H x 12" W x 15" D | 19 |
| OUTGOING MAIL | OM3 | 10" H x 12" W x 15" D | 1 |

Notes:

1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
 - a. At least one customer compartment shall be positioned less than 48" above finished floor (AFF).
 - b. No parcel locker (interior bottom shelf) shall be positioned less than 15" AFF.
 - c. No patron (tenant) lock shall be positioned more than 67" AFF.
 - d. No customer compartment (interior bottom shelf) shall be positioned less than 28" AFF.
 - e. The USPS Arrow lock shall be positioned 36"- 48" AFF.
2. This 4C mailbox can also be used for private applications.
3. The rough opening width for multi-unit 4C installations is provided using the Florence configurator: www.florencemailboxes.com/configurator.

PRODUCT SERIES: VERSATILE™ 4C FRONT LOAD MAILBOX

| | | | | |
|--|----------------|------------|---------------|----------|
| | MODEL | 4C11D-19 | REV | F |
| | SCALE | NONE | LAST REV DATE | 07/01/19 |
| | DRAWING NUMBER | 4C11D-19CS | DRAWN BY | RAK |