

(916) 273-1576
Fax (916) 635-0228
www.qualarc.com



QualArc
11300 Trade Center Dr., Ste. A
Rancho Cordova, CA 95742
U.S.A.

Scupper/Fountain Installation Instructions

- 1) Please keep in mind that these parts can be used in place of concrete, so they can be installed, in most cases, just like concrete scuppers, etc. Normal concrete fittings and sealants can be used.
- 2) We recommend you use a qualified pool or fountain installation company to install this product, as they have experience with concrete fittings and sealants.
- 3) Items are easily drilled or cut for plumbing. We recommend plumbing from the backside vs. the bottom. This helps prevent leaks by placing the fitting near the water line.
- 4) PVC fittings, with PVC glue, can be used to plumb. All fittings should be tight and sealed with a high quality pool plumbing sealant, gutter sealant or masonry sealant that is designed to handle constant exposure to water and pool chemicals, etc.
- 5) You may clean the scupper/fountain with a mild cleanser like Ajax and a soft sponge. You may also use Mr. Clean Magic Eraser or similar product.
- 6) If you use a matching planter as a bowl, please keep in mind that the inside bottom is exposed (unfinished), so you may want to cover the bottom with river pebbles or other media.

The preceding points were only suggestions - QualArc accepts no liability for any loss or damage caused by leaks, etc. due to faulty installation.